



Anglo Adhesives & Services Ltd.

INDUSTRIAL ADHESIVE MANUFACTURERS - CONTRACT FILLING AND PACKAGING

Anglo House The Airfield Dalby Road Melton Mowbray Leicestershire LE13 0BL UK

Tel: +44(0)1664 480866 - Fax: +44(0)1664 480963

E-mail: sales@anglo-adhesives.co.uk Web: www.anglo-adhesives.co.uk



SAFETY DATA SHEET

according to 1907/2006 EC, Article 31

Page 1 of 3

Revision 0
Revision date

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name Anti-Static Cleaner
Company Anglo Adhesives & Services Ltd
Anglo House
The Airfield
Dalby Road
Melton Mowbray
Leicestershire LE13 0BL
sales@anglo-adhesives.co.uk
www.anglo-adhesives.co.uk
Telephone +44 (0)1664 480866
Fax +44 (0)1664 480963
Emergency telephone number +44 (0)1664 480866

2 HAZARDS IDENTIFICATION.

Main hazards Irritating to eyes and skin.

3 . COMPOSITION / INFORMATION ON INGREDIENTS.

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Sodium hydroxide	0 - 3%	1310-73-2	215-185-5	C; R35
(N-Benzyl)-N,N,N-tributylammonium 4-dodecylbenzenesulfonate	0 - 3%		422-200-0	C; R34 Xn; R22 N; R51/53
Isopropanol (Propan-2-ol)	1 - 10%	67-63-0	200-661-7	F; R11 Xi; R36 R67

4. FIRST AID MEASURES

Skin contact Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.

Ingestion Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

5. FIRE FIGHTING MEASURES

Extinguishing media Carbon oxides.

Fire hazards Burning produces irritating, toxic and obnoxious fumes.

Protective equipment Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure limits**

Sodium hydroxide	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: 2
Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400 WEL 15 min limit ppm: 500	WEL 8-hr limit mg/m3: 999 WEL 15 min limit mg/m3: 1250

Engineering measures	Ensure adequate ventilation of the working area.
Respiratory protection	Wear: Suitable respiratory equipment.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Blue.
Odour	Pleasant.
Boiling point	100°C
Relative density	1.03
Water solubility	soluble in water.

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

Toxicological information	Irritating to eyes and skin.
----------------------------------	------------------------------

12. ECOLOGICAL INFORMATION

Ecotoxicity	No known adverse environmental effects.
--------------------	---

13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
----------------------------	---

14. TRANSPORT INFORMATION

Further information	The product is not classified as dangerous for carriage.
----------------------------	--

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Symbols Xi - Irritant



Risk phrases R36/38 - Irritating to eyes and skin.

16. OTHER INFORMATION

Text of risk phrases in Section 3.

R11 - Highly flammable.
R22 - Harmful if swallowed.
R34 - Causes burns.
R35 - Causes severe burns.
R36 - Irritating to eyes.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67 - Vapours may cause drowsiness and dizziness.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.