






DESIGN DEPARTMENT
PRODUCT SPECIFICATION SHEET

DOCUMENT NO: DES-FORM-A

ISSUE DATE: 6.1.14

DESIGN NAME:	EchoPanel@Mura
SUPPLIER:	Woven Image
ORIGIN:	Australia
COLOURS:	11
COMPOSITION:	100% PET (60% recycled)
WIDTH:	1210mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m²
PATTERN REPEAT:	N/A
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	N/A

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 5, Dry: 5
FIRE TEST:	AS3837 Classification: Group 1 (adhered to plasterboard) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions
SEAM SLIPPAGE:	N/A
USE:	 
VOC EMISSIONS:	ASTM D5116 Rate: < 0.02mg/m²/hr (7 days)
ENVIRONMENTAL:	 3 rd Party Certified: see website for details





**DESIGN DEPARTMENT
PRODUCT SPECIFICATION SHEET**

DOCUMENT NO: DES-FORM-A

ISSUE DATE: 5.5.11

DESIGN NAME:	EchoPanel®Mura Biline
SUPPLIER:	Woven Image
ORIGIN:	Australia/China
COLOURS:	1
COMPOSITION:	100% PET (60% recycled)
WIDTH:	1210mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m²
PATTERN REPEAT:	Embossed Vertical Stripe, Horizontal Repeat: 29.5cm
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	800m/design

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 5, Dry: 5
FIRE TEST AS PER MURA:	AS3837 Classification: Group 1 (adhered to plasterboard) Group 2 (adhered to Gyprock EC08™ Fire) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard) ASTM E84: Class 1 (adhered to Gyprock EC08™ Fire)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions
SEAM SLIPPAGE:	N/A
USE:	
VOC EMISSIONS:	 ASTM D5116 Rate: < 0.02mg/m²/hr (7 days)
ENVIRONMENTAL:	Greentag + LCA pending



DESIGN DEPARTMENT
PRODUCT SPECIFICATION SHEET

DOCUMENT NO: DES-FORM-A

ISSUE DATE: 21.3.13

DESIGN NAME:	EchoPanel®Mura Haku
DESIGNER:	Akira Isogawa
ORIGIN:	Australia/China
COLOURS:	2
COMPOSITION:	100% PET (60% recycled) Foil Print
WIDTH:	1210mm +/- 5mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m ² +/- 10%
PATTERN REPEAT:	Vertical: 20cm, Horizontal: 14.5cm See wovenimage.com for pattern match and application guide
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	800m/colour

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 4, Dry: 4/5
FIRE TEST:	AS3837 Classification: Group 1 (adhered to plasterboard) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions



USE:	
VOC EMISSIONS:	ASTM D5116 Rate: < 0.031mg/m ² /hr (7 days)



ENVIRONMENTAL:

For more information phone +61 2 9913 8668 or 1800 888 650 or visit www.wovenimage.com



DESIGN DEPARTMENT
PRODUCT SPECIFICATION SHEET

DOCUMENT NO: DES-FORM-A

ISSUE DATE: 3.8.12

DESIGN NAME:	EchoPanel@Mura Jaali
DESIGNER:	Rivet Design
ORIGIN:	Australia/China
COLOURS:	5
COMPOSITION:	100% PET (60% recycled)
WIDTH:	1210mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m ² +/- 10%
PATTERN REPEAT:	Vertical: 69cm, Horizontal: 58cm See wovenimage.com for pattern match and application guide
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	500m/colour

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 5, Dry: 5
FIRE TEST:	AS3837 Classification: Group 1 (adhered to plasterboard) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions



USE:	
VOC EMISSIONS:	ASTM D5116 Rate: < 0.02mg/m ² /hr (7 days)



ENVIRONMENTAL:

For more information phone +61 2 9913 8668 or 1800 888 650 or visit www.wovenimage.com





DESIGN DEPARTMENT
PRODUCT SPECIFICATION SHEET

DOCUMENT NO: DES-FORM-A

ISSUE DATE: 8.3.13

DESIGN NAME:	EchoPanel®Mura Kome
DESIGNER:	Akira Isogawa
ORIGIN:	Australia/China
COLOURS:	1
COMPOSITION:	100% PET (60% recycled) Pigment Print
WIDTH:	1210mm +/- 5mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m ² +/- 10%
PATTERN REPEAT:	Vertical: 20cm, Horizontal: 14.5cm See wovenimage.com for pattern match and application guide
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	500m/colour

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 5, Dry: 5
FIRE TEST:	AS3837 Classification: Group 1 (adhered to plasterboard) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions  
USE: VOC EMISSIONS:	ASTM D5116 Rate: < 0.02mg/m ² /hr (7 days)

ENVIRONMENTAL:







**DESIGN DEPARTMENT
PRODUCT SPECIFICATION SHEET**

DOCUMENT NO: DES-FORM-A

ISSUE DATE: 8.3.13

DESIGN NAME:	EchoPanel®Mura Nami
DESIGNER:	Akira Isogawa
ORIGIN:	Australia/China
COLOURS:	2
COMPOSITION:	100% PET (60% recycled)
WIDTH:	1210mm +/- 5mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m ² +/- 10%
PATTERN REPEAT:	Vertical: 72cm, Horizontal: 116cm See wovenimage.com for pattern match and application guide
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	800m/colour

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 5, Dry: 5
FIRE TEST:	AS3837 Classification: Group 1 (adhered to plasterboard) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions  
USE:	
VOC EMISSIONS:	ASTM D5116 Rate: < 0.02mg/m ² /hr (7 days)

ENVIRONMENTAL:







**DESIGN DEPARTMENT
PRODUCT SPECIFICATION SHEET**

DOCUMENT NO: DES-FORM-A

ISSUE DATE: 5.5.11

DESIGN NAME:	EchoPanel®Mura Otto
SUPPLIER:	Woven Image
ORIGIN:	Australia/China
COLOURS:	6
COMPOSITION:	100% PET (60% recycled)
WIDTH:	1210mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m²
PATTERN REPEAT:	Vertical: 2cm, Horizontal: 1.5cm See wovenimage.com for pattern match and application guide
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	500m/colour 1,000m/design

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 5, Dry: 5
FIRE TEST:	AS3837 Classification: Group 1 (adhered to plasterboard) Group 2 (adhered to Gyprock EC08™ Fire) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard) ASTM E84: Class 1 (adhered to Gyprock EC08™ Fire)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions
USE:	 
VOC EMISSIONS:	
ENVIRONMENTAL:	
	ASTM D5116 Rate: < 0.02mg/m²/hr (7 days)
	Greentag + LCA pending





DESIGN DEPARTMENT
PRODUCT SPECIFICATION SHEET

DOCUMENT NO: DES-FORM-A

ISSUE DATE: 3.2.12

DESIGN NAME:	EchoPanel®Mura Quattro
SUPPLIER:	Woven Image
ORIGIN:	Australia/China
COLOURS:	7
COMPOSITION:	100% PET (60% recycled)
WIDTH:	1210mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m ²
PATTERN REPEAT:	Vertical: 75cm, Horizontal: 58cm See wovenimage.com for pattern match and application guide
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	500m/colour 1,000m/design

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 5, Dry: 5
FIRE TEST:	AS3837 Classification: Group 1 (adhered to plasterboard) Group 2 (adhered to Gyprock EC08™ Fire) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard) ASTM E84: Class 1 (adhered to Gyprock EC08™ Fire)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions
SEAM SLIPPAGE:	N/A
USE:	 
VOC EMISSIONS:	ASTM D5116 Rate: < 0.02mg/m ² /hr (7 days)
ENVIRONMENTAL:	Greentag + LCA pending