




Hex Tile



258



295



151



108



273




551



362



579



542



444



442



908



500

For information


Mitchell Laminates
32-38 Redwood Drive
Dingley Vic 3172
Ph +61 3 9558 0800
Fax +61 3 9558 0557
sales@mitchelllaminates.com.au

Hex Tile

Specifications

Design Name	Hex Tile
Designer	Bang Design
Origin	Australia
Colours	13
Composition	100% PET (60% recycled)
Tile Dimensions	220mm +/- 0.5% x 200mm +/- 0.5%
Weight	2400g/m ² +/- 10%
Thickness	Approx. 12mm +/- 20%
Adhesive Backing	100% Acrylic

Performance

Colour Fastness to Light	ISO 105-B02-1994 Rating: 6-7 AS 2001.4.21-1970 Rating: 6-7
Fire Test	AS 1530.3 AS/NZS 3837 Rating: Group 3 Adhesive AS 1530.3
Care	Blot excess spills from material quickly. Wipe with a damp cloth. If stain persists, apply small quantities of carpet or upholstery shampoo solution with a damp cloth. Blot well with a clean cloth after each application of the solution. Warning, avoid excessive amounts of water. Ensure adequate ventilation if the product is likely to be subject to excessive moisture.
VOC Emissions	ASTM D5116 Rate: < 0.02 mg/m ² /hr (7 days) 
Features of Adhesive	100% Acrylic High temperature resistance High Tack Low VOC content and non ionic Easy liner removal Absolute aging resistance Very high water resistance