

Perspex[®] Brand 5 Year Guarantee Impact Modified Acrylic Sheet

Impact Modified Sheet

Lucite International guarantees that Perspex[®] Impact Modified acrylic sheet will comply in service with the performance specifications set out by Lucite International in the Appendix hereto for a period of five years subject to the following conditions:

- 1. The guarantee period of five years runs from the date of delivery of the sheet to the customer.
- 2. The guarantee covers the quality of the sheet as delivered and in particular:
 - 2.1 The sheet must be appropriately stored and transported prior to fabrication and installation.
 - 2.2 High standards of workmanship shall be used in fabrication and installation and Lucite International will not be liable for any failure attributable to poor standards of such workmanship.
 - 2.3 The guarantee does not cover any failure attributable to causes not usually associated with the normal use of Perspex[®] acrylic sheet and in particular does not apply to harm caused by chemical agents, cleaning fluids, unsuitable sealants or decorative materials.
- Lucite International must be given immediate notice of any complaint. Sufficient evidence of the complaint must be given to Lucite International and those authorised by it must be allowed adequate facilities to substantiate any complaint.
- 4. If any Perspex[®] acrylic sheet shall be shown to Lucite International's satisfaction to have failed to comply with the said performance specifications within the stipulated time limit Lucite International shall replace the failed sheet with an equivalent amount of Perspex[®] acrylic sheet or other suitable alternative sheet to be delivered free of charge by Lucite International to a delivery point to be nominated by the customer, but Lucite International shall under no circumstances be responsible for any other damage or loss howsoever arising whether directly or indirectly.
- 5. Lucite International gives no guarantee or warranty express or implied in relation to Perspex[®] acrylic sheet apart from the guarantee given herein.
- This guarantee and all the terms thereof shall apply to all deliveries of Perspex[®] acrylic sheet supplied by Lucite International until the guarantee is revoked by either of the parties.

Revocation may be effected by either party serving on the other notice in writing to that effect at any time.

T: +44 (0) 1254 874000 F: +44 (0) 1254 874098 info@perspex.com www.perspex.com

- Revocation shall not affect deliveries of sheet made prior to the date of revocation which shall continue to be fully covered by the terms of this guarantee.
- If the customer shall bring any claim under this guarantee it shall produce documentary evidence to Lucite International's satisfaction that the sheet in question is Perspex[®] acrylic sheet made by Lucite International.

Appendix

Outdoor ageing behaviour of Perspex[®] Impact Modified acrylic sheet:

1. Elastic Modulus

The rigidity of Perspex[®] acrylic will remain substantially unchanged in service. This means that the elastic modulus of a sample cut from a section of Perspex[®] acrylic will not be less than 2500 MPa as delivered and for five years after delivery (test method: ISO 178 measured on specimens removed from the exposed Perspex[®] acrylic installation).

2. Tensile Strength

Perspex[®] acrylic will suffer no unacceptable change in brittleness. This means that the tensile strength as delivered and for five years after delivery of a sample cut from a section of Perspex[®] acrylic sheet will not be less than 50 MPa. (test method: ISO R 527 measured on specimens, removed from the exposed Perspex[®]).

3. Light transmission

The light transmission for Perspex[®] Impact Modified sheet will not fall below 85% (test method: ASTM D 1003 when measured using a cleaned and polished flat sample of 1mm thickness taken from the exposed sheet).

LUCITE INTERNATIONAL 2016

Perspex[®] and Lucite[®] are registered Trade Marks owned by Lucite International UK Limited.

